







PRODUCT MANUAL















APPLICATIONS

Signboard light boxes, signage, advertising signs, decoration and other areas

MOUNTING METHOD

Thermally conductive adhesive or screw fixing.

- Single color available in 3 different temperatures, Cool, Warm, and Neutral white.
- Suitable for double-sided light boxes from 4" to 9" thick.
- ❷ High Power LED.
- Single or Two LEDs can be cut to suit different light box lengths.
- Waterproof


PRODUCT STRUCTURE


41" (105 cm) 1.18" (30 mm) 39.5" (100.33 cm)

SIDE VIEW

0.47" (12 mm)













LARGOLED 41" CW6500K IP65 HIH POWER LED BAR SURFACE-MOUNTED LED CHANNEL

SKU: 2800LRG251-1001 SIZE: 41" X 1.2" X 0.8"

COLOR LED: Cool White 6500K,

VOLTAGE: 24VDC **POWER:** 27Watts

BEAM ANGLE: 10° x 45° NUMBER OF LEDS: 18

RATING: IP65

UL LISTED: E363518

LARGOLED 36.7" CW6500K IP65 HIH POWER LED BAR SURFACE-MOUNTED LED CHANNEL

SKU: 2800LRG251-1002 SIZE: 36.7" X 1.2" X 0.8"

COLOR LED: Cool White 6500K

VOLTAGE: 24VDC **POWER:** 24Watts


BEAM ANGLE: 10° x 45° **NUMBER OF LEDS:** 16

RATING: IP65

UL LISTED: E363518








































THANK YOU

305-652-2599













